



ARUN

AN ISO 9001 : 2008 CERTIFIED COMPANY



TWO FOR ONE TWISTER (WITH MAXIMUM POWER SAVING)
60 mm POT DIAMETER

TECHNICAL SPECIFICATIONS

Structural Data	9 Spindles per Channel	10 Spindles per Channel
Spindle wharves	19.5 / 20.5 / 22.5 / 25 mm	19.5 / 20.5 / 22.5 / 25 mm
Spindle pitch	140 mm	124 mm
Traverse length	100 mm	83 mm
Take up package weight	500 to 550 gm	400 to 450 gm
Mechanical Data		
Max. spindle speed (Mechanical)	12000 rpm	12000 rpm
Twist range	400 to 4000 tpm	400 to 4000 tpm
Direction of twist	'S' or 'Z' Changeable	'S' or 'Z' Changeable
Spindle drive	Tangential belt drive	Tangential belt drive
Supply package / Feed package		
Type	Aluminum cops with three grooves	Aluminum cops with three grooves
Size	(Ø32 x Ø36 x 220 / 240 l) mm	(Ø32 x Ø36 x 220 / 240 l) mm
Take up package / Delivery package		
Package size	Ø123 x 100 mm flanged roll	Ø123 x 83 mm flanged roll
Traverse		
Mechanism	Cam assembly with anti-pattern device	Cam assembly with anti-pattern device
Size	100 mm parallel	83 mm parallel
Operating system	D.O.L. Starter	D.O.L. Starter

Technical specifications are subject to change without specific prior notice due to continuous development

MACHINE DIMENSIONS - 9 SPINDLES PER CHANNEL

No. of Spindles	No. of Sections	Length (ft)	Width (ft)	Height (ft)	Motor (hp)	Nos
360	10	47' 6"	2	5' 10"	2	2
396	11	52'	2	5' 10"	2	2
432	12	56' 6"	2	5' 10"	2.5	2
468	13	61'	2	5' 10"	3	2
504	14	65' 6"	2	5' 10"	4	2
540	15	70'	2	5' 10"	4	2

MACHINE DIMENSIONS - 10 SPINDLES PER CHANNEL

No. of Spindles	No. of Sections	Length (ft)	Width (ft)	Height (ft)	Motor (hp)	Nos
400	10	47' 6"	2	5' 10"	2	2
440	11	52'	2	5' 10"	2	2
480	12	56' 6"	2	5' 10"	2.5	2
520	13	61'	2	5' 10"	3	2
560	14	65' 6"	2	5' 10"	4	2
600	15	70'	2	5' 10"	4	2



ARUN

TEXTILE ENGINEERS PVT. LTD.

Reliable Partners In Progress

45, Jasukaka Wadi, Opp. Leprosy Hospital, A.k. Road, Surat-395008. (Gujarat) INDIA.

Tel. +91-261-2552222, 2550061 Fax: +91-261-2551836

Website : www.aruntexeng.com Email : info@aruntexeng.com