



HIGH SPEED VERTICAL UP-WINDING MACHINE



ARUN

TEXTILE ENGINEERS PVT. LTD.



TECHNICAL SPECIFICATIONS

No. of Spindles	: 32-40-48-64-80-96
Type of Spindles / Bolster	: Taper Spindle / 780 Inserts
Spindle R.P.M.	: 3000-4000 RPM
Traverse Speed	: 15 Full Strokes per minute, Adjustable
Feed Package	: Upto 200 MM Diameter and 450 MM Height
Take up Package	: Ranging from 75 MM to 125 MM in length and upto 85 MM Flange Diameter
Belts	: Endless Nylon Sandwich Belt
Gear Box	: Grooved Solid Drum type.
Traverse Length	: 75 MM to 150 MM adjustable

MOTOR

(A) For 32, 40 and 48 Spindle Models	: One Motor of 0.5 H.P. 900 R.P.M. Flange Mounted
(B) For 64, 80 and 96 Spindle Models	: One Motor of 0.5 H.P. 900 R.P.M. Flange Mounted for spindle Drive and One Motor of 0.5 H.P. 1400 R.P.M. Flange Mounted for traverse Motion

DIMENSIONS

No. of Spindles	32	40	48	64	80	96
Length in Feet	11	13	15	18	21	24
Width in Feet	3	3	3	3	3	3
Height in Feet	5	5	5	5	5	5

SPECIAL FEATURES

- (1) Each Spindles is Provided with Ceramic Tensioning Device for proper package Build and for Removal of Uneven Unwinding Tensions.
- (2) Yarn oiling device is provided with stainless steel trough and stainless steel rollers.
- (3) Hard chrome plated hooks and guides provided in all yarn passages.
- (4) Prompt after sales service.



ARUN

TEXTILE ENGINEERS PVT. LTD.

45, Jasukaka Wadi, Opp. Leprosy Hospital, A.K. Road, Surat-395 008. (Guj.) INDIA.
Phone : 612222, 648884 Fax : 91-261-611836.

OUR NEW TELEPHONE NO.



552222
550061
544368

FAX NO. 91 - 0261- 551836